



12X Speed PTZ Camera

12x Optical Zoom PTZ 10x Digital Zoom
High Resolution 580 TVL
220 Preset Position
360° Endless Rotation
8 Privacy Masking Zones
OSD for Camera Control
Max 250° sec Speed on Preset Mode
Vandal-Proof Poly Carbonate Clear Dome Cover IP66
Password Protection



360° Endless Rotation

Pant / Tilt

- Pan Rotation Angle: 360° Endless
- Pan Speed: Manual : 0.05° ~ 150° /sec (64step) / Preset : Max 250°/sec
- Tilt Rotation Angle: -2° ~ 90°
- Tilt Speed: Manual: 0.05° ~ 150°/sec (64pasos) / Preset: Máx 250°/sec
- System Accuracy: 0.05°

Function

- Preset: 220 positions with 16-character
- Group TourMax. 8 Programmable group tours
- Auto Scan: Programable Auto scan
- Pattern: 8 Programmable Patterns (total 480 seconds)
- Sector: 8 selectable Sectors with 16 characters
- Home Position & Recover: Yes(Preset / Tour / Pattern / Scan)
- WDR: N/A - SSSNR: Yes
- DSS: On / Off - BLC: On / Off - HLC: On / Off
- Day & Night: AUTO / DAY / NIGHT
- Alarm Input: 4 alarms(with various programmable states)
- Alarm Actions: Activate preset, Group Tour, Pattern
- Aux Output: N/A
- Communication: RS-485

Camera Module

- Image Sensor: 1/4" Sony Super HAD CCD
- Total Image Pixels: NTSC : 811(H) x 508(V) 410K
- Horizontal Resolution: Color : 580TVL, B/W : 680TVL
- Lens: 12x f=3.94~46.05mm(F 1.67~1.88) (Digital : 16X / Total :192X)
- Min. Illumination: 0.2Lux / F1.6(Color : 50IRE) 0.04Lux / F1.6 (B/W : ICR ON)
- Luminance S/N Ratio: More than 52dB
- Video Output: Composite video output 75Ω Terminated

Power

- Power Consumption: AC24V 0.7A 16W Max(1.1A 24W With Heater), DC12V 0.8A 10W Max(1.3A 16W With Heater)
- Power Supply: AC24V 50/60hz 1.5A(With Heater) / DC12V 1.7A(With Heater)